

SERVICE SCHEDULE



IMT GREASE LUBRICATED AXLE TYPES F22, FE22, FE24

ERVICE SCHEDULE			Periodic checks	
Mileage intervals	After first 5000kms		Every	Every
Vhich ever comes first >			30,000km	120,000km
Time intervals	After first	Every	Every	Every
	month	Month	3 months	12 months
			INSPECTION	IS
lemove hub cap and inspect grease around outer bearing and in hub cap for ontamination				•
Clean and repack bearings and hub with fresh grease				•
				_
Check condition of taper roller bearings, Replace if necessary				•
*original equipment uses SAF Li Lube grease GENERAL for wear / damage				
*original equipment uses SAF Li Lube grease GENERAL for wear / damage	•	•		•
*original equipment uses SAF Li Lube grease GENERAL for wear / damage Check wheel bearings for excessive play, adjust as required (Min 0.25, Max 0.16mm)	•	•		
*original equipment uses SAF Li Lube grease GENERAL for wear / damage Check wheel bearings for excessive play, adjust as required (Min 0.25, Max 0.16mm) Chech hubs for correct rotaion, loss of lubricant and free of bearing noise		•		
*original equipment uses SAF Li Lube grease GENERAL for wear / damage Check wheel bearings for excessive play, adjust as required (Min 0.25, Max 0.16mm) Chech hubs for correct rotaion, loss of lubricant and free of bearing noise Check brake linings for wear				
*original equipment uses SAF Li Lube grease GENERAL for wear / damage Check wheel bearings for excessive play, adjust as required (Min 0.25, Max 0.16mm) Chech hubs for correct rotaion, loss of lubricant and free of bearing noise Check brake linings for wear Check brakes for correct adjustment		•		
*original equipment uses SAF Li Lube grease				

Special service conditions;

Vehicles operating in off highway / harsh conditions; service at suitably reduced time intervals to suit the vehicle operation